



10/100 5 PORT Ethernet Switch

Model no. L05-S10AZ

Product Description

L05-S10AZ is a 5/-port 10/100Mbps Fast Ethernet Switch provides 5 10/100Mbps Auto-Negotiation RJ45 ports. All ports support Auto MDI/MDIX function, eliminating the need for crossover cables or Uplink ports. The Switch is Plug-and-Play and each port can be used as general ports or Uplink ports and can be simply plugged into a server, a hub or a switch, using straight cable or crossover cable

Product Features

- ❖ Supports IEEE 802.3x flow control for Full Duplex mode and backpressure for half-duplex mode
 - ❖ Supports MAC address auto-learning and auto-aging
 - ❖ LED indicators for monitoring power, link, activity
 - ❖ Plastic case, desktop or wall-mounting design
 - ❖ External Power Adapter supply
-

Product Specification

| | |
|---|--|
| Standard | IEEE802.3, 802.3u, 802.3x, CSMA/CD, TCP/IP |
| Basic Function | Wire-speed Performance Mac Address Auto-Leading And Auto-AGING IEEE802.3x flow control for Full-Duplex Mode and back pressure for Half-Duplex Mode |
| Mac Address Table | 1K |
| Network Media | 10Base-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100U STP (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100U STP (maximum 100m) |
| LED | Power, Link/Act |
| Port | 5 10/100Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX) |
| Transmission Method | Store-and-Forward |
| Media | 100BASE-TX: UTP/STP Cat. 5 |
| Backplane Bandwidth | 1Gbps |
| Operating Temperature | 0 ~ 55°C |
| Storage | -40° C~70° C (-40°F~158°F) |
| Humidity | 5 ~ 95% non-condensing |
| Power External DC Power adapter (linear) | DC9V, 800MA; |